


# FIRENZE





1,25 KG 



Proiettore professionale per illuminazione architettonica per utilizzo esterno. Corpo e base in alluminio verniciato con polveri epossidiche previo trattamento di fosfocromatazione ad alta resistenza alle nebbie saline. Vetro di protezione temperato. Guarnizioni in silicone. Viti fissaggio anello in acciaio inox. Riflettore in alluminio ossidato. Pressacavi in ottone cromato. Utilizzo di moduli LED IOB (220/240V).

Professional projector for outdoor architectural lighting. Aluminium housing and base, epoxy powder painting before a specific washing process called "phospho- chromate", resistant to saline mists. Tempered protective glass. Silicone gasket. Stainless steel screws. Oxidized aluminium reflector. Chromed brass cable-glands. Use of IOB LED modules (220 / 240V).

CODE	LUMEN NOM			
	LED	W	3000°K	4000°K
79020 	IOB	20	2000	2100
79030 	IOB	30	3000	3100

## ■ COLOR CODE

-  **10** - frosted alu
-  **32** - frosted white
-  **33** - frosted black

## • LED COLOR CODE

**3000°K**- 85

**4000°K**- 85

## ▲ REFLECTOR CODE

**15°** - REFLECTOR BEAM

**38°** - REFLECTOR BEAM

**60°** - REFLECTOR BEAM

# FIRENZE



Proiettori professionali in alluminio per illuminazione architettuale.

Professional projector in aluminium for architectural illumination.