



SKY LIGHT OPTICS



POWER SUPPLY
220/240V-50/60Hz

Professional adjustable recessed downlight.
Horizontal rotation 356°, vertical movement 60°.
Reflector with pure aluminum 99.9% bright finish for maximum light recovery and control. Painted aluminium body. Anodized or black painted aluminium heatsink.
The COB LED version is proposed with CRI 85 color rendering also in dimmable version and supplied complete with separate power supply. On request it is possible to have CRI 95 color rendering and LED colors for special applications.

Professional adjustable recessed downlight.
Horizontal rotation 356°, vertical movement 60°.
Reflector with pure aluminum 99.9% bright finish for maximum light recovery and control. Painted aluminium body. Anodized or black painted aluminium heatsink.
The COB LED version is proposed with CRI 85 color rendering also in dimmable version and supplied complete with separate power supply. On request it is possible to have CRI 95 color rendering and LED colors for special applications.

CODE	LUMEN NOM			
	LED	W	3000°K	4000°K
33TCR11120AC	IOB	20	2200	2400
33TCR11130AC	IOB	30	3300	3600
33TCR11140AC	IOB	40	4400	4800
33TCR11125	COB	25	3770	3900
33TCR11135	COB	35	4680	4840
33TF15ACPAR	IOB	15	1650	1800

■ COLOR CODE

- 33 - frosted black
- 10 - frosted alu

• LED COLOR CODE

- 3000°K- 85
- 4000°K- 85

▲ REFLECTOR CODE

- 10° - REFLECTOR BEAM
- 24° - REFLECTOR BEAM
- 45° - REFLECTOR BEAM