



## MINITU



Mini proiettore orientabile da binario o con base per parete/soffitto, completo di modulo LED IOB. Orientabile sul piano orizzontale 350° e sul piano verticale 90°. Corpo in alluminio verniciato. Riflettore brillantato con puro alluminio 99,9%, disponibile con apertura del fascio luminoso 15° - 24° - 36°. Schermo di protezione trasparente.

Mini truck-mounted adjustable projector with multi ignition adapter included, or with base for wall-ceiling, complete with IOB LED module. Adjustable on the horizontal plane 350° and on the vertical plane 90°. Body in painted aluminium. Reflector with 99,9% pure aluminium bright finishing, with light beam opening 15° - 24° - 36°. Transparent protection screen.





0,400 KG 



POWER SUPPLY  
220/240V-50/60Hz


## ACCESSORI / ACCESSORIES

**Ref. Beam SPOT**



15° Beam

**Refl. Beam Medium**



24° Beam

**Refl. Beam Large**

36° Beam

CODE	LUMEN NOM			
	LED	W	3000°K	4000°K
57408R WITH ADAPTER FOR TRACK 	COB	8	800	900
57408B WITH BASE 	COB	8	800	900

**■ COLOR CODE**

-  **32** - frosted white
-  **33** - frosted black

**• LED COLOR CODE**

- 3000°K**- 85
- 4000°K**- 85

**▲ REFLECTOR CODE**

- 15°** - REFLECTOR BEAM
- 24°** - REFLECTOR BEAM
- 36°** - REFLECTOR BEAM