


MIRO



Proiettore orientabile in alluminio verniciato. Versione innovativa con LED IOB. Formato dalla sola unità ottica completo di riflettore con fasci di luce 15° - 36° - 60° e dissipatore non avendo necessità di un alimentatore separato. Rotazione sull'asse orizzontale 355° e movimento sull'asse verticale 90°.

Adjustable projector in painted aluminium. innovative version with IOB LED module. It consists of only the optical unit, a reflector with light beams of 15° - 36° - 60°, and an heatsink, without the need of a power supply. Rotation on the horizontal plane 355° and movement on the vertical plane 90°.




400 GR



POWER SUPPLY
220/240V-50/60Hz

ACCESSORI / ACCESSORIES



ADATTATORE PERBINARIO

Adattatore per collegamento binario EUROTRACK
Adapter for track connection



BASE

Base montaggio Parete/Soffitto
Wall/Ceiling die cast aluminium mounting base

| CODE | LUMEN NOM | | | | |
|-------------------------------------|-----------|----|--------|----------------------|--------|
| | LED | W | 3000°K | DIMENSIONS A-B mm | WEIGHT |
| 77020R WITH ADAPTER FOR TRACK | IOB | 20 | 2200 | 95X95X95 | 400 GR |
| 77020B WITH BASE | IOB | 20 | 2200 | 95X95X95 | 400 GR |
| 77030R WITH ADAPTER FOR TRACK | IOB | 30 | 3300 | 95X95X95 | 400 GR |
| 77030B M WITH BASE | IOB | 30 | 3300 | 95X95X95 | 400 GR |

■ COLOR CODE

- 10 - frosted alu
- 32 - frosted white
- 33 - frosted black

● LED COLOR CODE

- 3000°K- 85
- 4000°K- 85

▲ REFLECTOR CODE

- 15° - REFLECTOR BEAM
- 36° - REFLECTOR BEAM
- 60° - REFLECTOR BEAM

MIRO

Proiettore orientabile d'avanguardia dal design innovativo, prodotto in tre finiture di colore: bianco, nero e grigio.

Avant-guard adjustable projector of innovative design produced in three finishes, black, white and grey.