


OTTO P.



1 KG



POWER SUPPLY
220/240V-50/60Hz

Mono and Bi emission wall light. Square shape. High light emission with innovative IOB LED (220/240V). Ideal for architectural buildings illumination. Extruded aluminium body. Epoxy powder painting resistant to atmospheric agents after a specific washing process called "phospho-chromate". Protective tempered transparent glasses.
M - Monoemission B - Biemission

Mono and Bi emission wall light. Square shape. High light emission with innovative IOB LED (220/240V). Ideal for architectural buildings illumination. Extruded aluminium body. Epoxy powder painting resistant to atmospheric agents after a specific washing process called "phospho-chromate". Protective tempered transparent glasses.
M - Monoemission B - Biemission

CODE	LUMEN NOM				HOLE DIMENSIONI	DIMENSIONS A-B mm
	LED LAMP	W	3000°K	4000°K		
OW10M	1XGU10				190X100X100	190X100X100
OW10B	2XGU10				190X100X100	190X100X100
OW17M	IOB	1X7	770	840	190X100X100	190X100X100
OW27B	IOB	2X7	1540	1680	190X100X100	190X100X100

COLOR CODE

- 10 - frosted alu
- 32 - frosted white
- 33 - frosted black
- 75 - corten

LED COLOR CODE

- 3000°K- 85
- 4000°K- 85

REFLECTOR CODE

- 15° - REFLECTOR BEAM
- 38° - REFLECTOR BEAM
- 60° - REFLECTOR BEAM

OTTO P.



Single and double emission wall light, square shape, suitable for external use, ideal as architectural source of light for environments such as shops, building facades, public and private entrances.

Single and double emission wall light, square shape, suitable for external use, ideal as architectural source of light for environments such as shops, building facades, public and private entrances.