


TUBO IP






2,2 - 3,5KG 







C.R.I. > 95 **EMERGENCY 1 or 3 hr** POWER SUPPLY 220/240V-50/60Hz

Professional ceiling light with LED light source. Extruded aluminium painted body. LED optical system complete with aluminium reflector with 99,9% pure aluminium bright finishing for the maximum luminous efficiency and control of the light emission. Light beams 15°-38°-60° Use of LED module COB. Built-in power supply.

Professional ceiling light with LED light source. Extruded aluminium painted body. LED optical system complete with aluminium reflector with 99,9% pure aluminium bright finishing for the maximum luminous efficiency and control of the light emission. Light beams 15°-38°-60° Use of LED module COB. Built-in power supply.

CODE	LUMEN NOM					HOLE DIMENSIONI	DIMENSIONS A-B mm
	LED	W	3000°K	4000°K			
4512 	COB	12	2000	2080	150X380	150X380	
4518 	COB	18	2800	2920	150X380	150X380	
4525 	COB	25	3770	3900	150X380	150X380	

■ COLOR CODE

-  **10** - frosted alu
-  **32** -
-  **33** - frosted black
-  **75** - corten

• LED COLOR CODE

- 2200°K**- 85
- 3000°K**- 85
- 3500°K**- 85
- 4000°K**- 85
- 5000°K**- 85

▲ REFLECTOR CODE

- 15°** - REFLECTOR BEAM
- 38°** - REFLECTOR BEAM
- 60°** - REFLECTOR BEAM