


FLOORING INOX 10



Corpo ed anello bloccaggio vetro in acciaio inox. Guarnizione in silicone. Carico statico 1000 kg. Carrabile alla velocità minima di 20 km/h. Vetro di protezione temperato spessore 5mm. Pozzetto di alloggiamento faro in materiale termoplastico. Sorgenti luminose a led statico e RGB

Stainless steel housing and trim. Silicone gasket. Static load 1000kg. Minimum speed drive 20km/h. 5mm tempered protective glass. Thermoplastic housing. Light sources static or RGB LED



0,700 GR 



ACCESSORI / ACCESSORIES



C1 - COVER FLOORING INOX 10 - MONO-EMISSION



C2 - COVER FLOORING INOX 10 - BI-EMISSION



C3 - COVER FLOORING INOX 10 - TRIPLE-EMISSION



CM - COVER FLOORING INOX 10 - 360° EMISSION

CODE

LUMEN NOM

	LED	W	3000°K	DIMENSIONS A-Bmm	WEIGHT	• LED COLOR CODE
261007AC_	IOB	7	600	107X140X75	800 GR	2200°K- 85
261050GU10_	GU10			107X140X75	700 GR	3000°K- 85 4000°K- 85

Inox A316 / A316 Stainless Steel

geneX
GENERAZIONI DI LUCE

FLOORING INOX 10

Faro incasso pavimento da esterni in acciaio INOX.

Outdoor recessed floor floodlight in stainless steel.