



TUBO IP POWER





1.9 KG 







Faro da soffitto professionale con sorgente luminosa a LED con elevato flusso luminoso. Corpo in alluminio estruso e dissipatore di calore esterno verniciato. Sistema ottico LED completo di riflettore in alluminio brillantato con puro alluminio 99,9% per il massimo recupero e controllo dell'emissione luminosa, con tre fasci luminosi 15°, 38°, 60°. Modulo LED COB. Alimentazione integrata.

Professional ceiling light with LED light source. Extruded aluminium and heat sink painted body. LED optical system complete with aluminium reflector with 99,9% pure aluminium bright finishing for the maximum luminous efficiency and control of the light emission. Light beams 15°-38°-60°. Use of LED module COB. Built-in power supply.

CODE	LUMEN NOM			
	LED	W	3000°K	4000°K
4535P 	COB	35	4800	4900
4540P 	COB	40	5420	5600

COLOR CODE

-  **10** - frosted alu
-  **32** - frosted white
-  **33** - frosted black
-  **75** - corten

LED COLOR CODE

- 2200°K**- 85
- 3000°K**- 85
- 3500°K**- 85
- 4000°K**- 85
- 5000°K**- 85

REFLECTOR CODE

- 15°** - REFLECTORBEAM
- 38°** - REFLECTORBEAM
- 60°** - REFLECTORBEAM

