FIRENZE



1,25 KG

IP66 IK05 Integrated On Board LED 220V AC FLICKER FREE 30.000 naval use TRIAC

POWER SUPPLY
220/240V-50/60Hz

Proiettore professionale per illuminazione architetturale per utilizzo esterno. Corpo e base in alluminio verniciato con polveri epossidiche previo trattamento di fosfocromatazione ad alta resistenza alle nebbie saline. Vetro di protezione temperato. Guarnizioni in silicone. Viti fissaggio anello in acciaio inox. Riflettore in alluminio ossidato. Pressacavi in ottone cromato. Utilizzo di moduli LED IOB (220/240V).

Professional projector for outdoor architectural lighting. Aluminium housing and base, epoxy powder painting before a specific washing process called "phospho- chromate", resistant to saline mists. Tempered protective glass. Silicone gasket. Stainless steel screws. Oxidized aluminium reflector. Chromed brass cable-glands. Use of IOB LED modules (220 / 240V).

CODE	LUMEN NOM		
	LED	W	3000°K
79020 ■.●.▲	IOB	20	2000
79030 ■.●.▲	IOB	30	3000

■ COLOR CODE

- **10** - frosted alu
- **32** - frosted white
- **33** - frosted black

● LED COLOR CODE

- **3000°K**- 85
- **4000°K**- 85

▲ REFLECTOR CODE

- **15°** - REFLECTOR BEAM
- **38°** - REFLECTOR BEAM
- **60°** - REFLECTOR BEAM

FIRENZE

Proiettori professionali in alluminio per illuminazione architetturale.

Professional projector in aluminium for architectural illumination.