


## TUBO LED EM



Properties: Non maintained operation, Self-test as per IEC, 3h rated duration, Operation time selectable with plug (duration link) 3-pole technology: 2-pole LED module changeover Constant power output, Two-colour status display LED, "Rest mode" function, Electronic multi-level charge system, Deep discharge protection, Short-circuit-proof battery connection Status of the battery, Status of the LED, Charge condition, Function test, Duration test. Available in different heights and (on request) protection glass fixed in front of the reflector, inside the fixture.

Properties: Non maintained operation, Self-test as per IEC, 3h rated duration, Operation time selectable with plug (duration link) 3-pole technology: 2-pole LED module changeover Constant power output, Two-colour status display LED, "Rest mode" function, Electronic multi-level charge system, Deep discharge protection, Short-circuit-proof battery connection Status of the battery, Status of the LED, Charge condition, Function test, Duration test. Available in different heights and (on request) protection glass fixed in front of the reflector, inside the fixture.

CODE	LUMEN NOM				HOLE DIMENSIONS	DIMENSIONS A-B mm
	LED	W	3000°K	4000°K		
4025 EM 24	COB 45°	25	3700	3900	240X220	240X220
4025 EM 16	COB 45°	25	3700	3900	240X220	240X220



3.5 KG

POWER SUPPLY  
220/240V-50/60Hz

## ACCESSORI / ACCESSORIES



## M3F

Accessory for suspension, made of 3 steel wires length 1,50m, electric wire 3x1mm2 transparent length 1,50m and die-cast aluminium base.

Accessory for suspension, made of 3 steel wires length 1,50m, electric wire 3x1mm2 transparent length 1,50m and die-cast aluminium base.

## ■ COLOR CODE

- 10 - frosted alu
- 32 - frosted white
- 33 - frosted black

## • LED COLOR CODE

- 3000°K- 85
- 3500°K- 85
- 4000°K- 85